



*Total Solution Provider in Saw Device*

---

# SA462BM

CDMA 450 C-Band, RF-Rx SAW Filter  
Revision 0: April 2005



- Electrical Characteristics
  - Package Dimensions
  - Testing Environment
  - Frequency Characteristics
- 

**SAWNICS Inc.**

460 Cheonheung-ri, Seonggeo-eup, Cheonan-si, Chungcheongnam-do, 330-836 / Korea.  
Tel: +82 41 550 9372 / Fax: +82 41 550 9399 / [www.sawnics.com](http://www.sawnics.com)

## □ Electrical Characteristics

### Maximum Ratings


Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+80
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	27
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	M			
Length x Width	mm <sup>2</sup>	-	3.0 x 3.0	-
Height	mm	-	-	1.3

### Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	462.5	-
Insertion Loss within 460.0 ~ 464.8 MHz	dB	-	3.0	3.5
<b>Attenuation:</b>				
0.3 ~ 450.0 MHz	dB	40	48	-
450.0 ~ 454.8 MHz	dB	35	45	-
485.0 ~ 505.0 MHz	dB	40	53	-
505.0 ~ 1200.0 MHz	dB	30	37	-
1200.0 ~ 2000.0 MHz	dB	20	32	-
VSWR within 460.0 ~ 464.8 MHz	-	-	2.0	2.4

**Notes :** (1) No Matching Network


**Package Dimensions**



Marking Descriptions	
A	CDMA450 Application
9	Series Number
X	Date Code(Year)
Y	Date Code(Month)

Pin Description	
A, C, D, F	Ground
E	In
B	Out



**Testing Environment**





Source & Load Impedance: 50 Ω

**Frequency Characteristics**

Frequency Response



### VSWR



### Smith Chart

